

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
9 October 2003 (09.10.2003)

PCT

(10) International Publication Number
WO 03/082644 A1

(51) International Patent Classification⁷: B60T 8/00 (74) Agents: BOTTERO, Carlo et al.; Pirelli S.p.A., Viale Sarca, 222, I-20126 Milano (IT).

(21) International Application Number: PCT/EP03/03088 (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 25 March 2003 (25.03.2003) (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(25) Filing Language: English (30) Priority Data: PCT/EP02/03498 28 March 2002 (28.03.2002) EP

(26) Publication Language: English

(71) Applicant (for all designated States except US): PIRELLI PNEUMATICI S.p.A. [IT/IT]; Viale Sarca, 222, I-20126 Milano (IT).

(72) Inventors; and (75) Inventors/Applicants (for US only): BRUSAROSCO, Massimo [IT/IT]; Pirelli Pneumatici S.p.A., Viale Sarca, 222, I-20126 Milano (IT). FIORAVANTI, Anna, Paola [IT/IT]; Pirelli Pneumatici S.p.A., Viale Sarca, 222, I-20126 Milano (IT). MANCOSU, Federico [IT/IT]; Pirelli Pneumatici S.p.A., Viale Sarca, 222, I-20126 Milano (IT).

(54) Title: METHOD AND SYSTEM FOR MONITORING A TYRE DURING THE RUNNING OF A VEHICLE



WO 03/082644 A1

(57) Abstract: A method for monitoring the behavior of a tyre during running, the method comprising the steps of: acquiring and storing, at least temporarily, a first curve representing the acceleration profile of a first point of the tread area of said tyre, located on a meridian plane of said tyre; acquiring and storing, at least temporarily, at least a second curve representing the acceleration profile of a second point of the tread area of said tyre, located substantially on said meridian plane; comparing said first and second curves, or parameters derived thereof; determining the behavior of said tyre from said comparison.